LIMITED WARRANTY STATEMENT PHOTOVOLTAIC MODULE PRODUCTS



1.Limited Product Warranty - 12 Years Repair, Replacement or Refund Remedy

SpolarPV Technology Co., Ltd (thereafter as "SpolarPV") warrants to the original buyer (the "Buyer") that the modules shall be free from defects in materials and workman ship that have an effect on module functionality under normal application, installation, use and service conditions as specified in SpolarPV's standard product documentation.

SpolarPV guarantees that the module will maintain the mechanical integrity and stability in accordance with approved operation methods described in our installation instructions; the glass of a module will maintain its integrity provided there are no indications of localized impacts or external forces; and that the cable and connector plug of a module will remain safe and operational provided modules are professionally installed. Any damages caused by abrasion, improper installation or animals are exempt from this warranty.

Claims under the warranty can only be accepted if the Buyer can provide proof that the malfunctioning or nonconformity of a module results exclusively from defects in materials and/or workmanship under normal application, installation, use and service conditions specified in SpolarPV's standard product documentation. Any color change on module or any other changes on module appearance do not represent defects, insofar as the change in appearance does not stem from defects in material and/or workmanship, and does not cause degradation of functionality of the module. If the product fails to conform to this warranty, SpolarPV will, at its option, either repair or replace the product, or provide an appropriate residual market value of the product(s) as compensation.

Our goods come with guarantees that cannot be excluded under the Australian Consumer Law. You are entitled to a replacement or refund for a major failure and compensation for any other reasonably foreseeable loss or damage. You are also entitled to have the goods repaired or replaced if the goods fail to be of acceptable quality and the failure does not amount to a major failure.

2.Limited Peak Power Warranty - Limited Remedy

- **2.1** For poly crystalline and mono crystalline module products, SpolarPV guarantees the first year power degradation is no more than 2% from its nameplate power. From year 2 to year 25, the actual annual power decline will be no more than 0.55%. By the end of year 25, the actual power output will be no less than 84.8% of the labeled power output.
- **2.2** The actual power output of the module shall be determined for verification using Standard Testing Conditions only. The actual power output measurement is either carried out by a SpolarPV facility or by a SpolarPV recognized 3rd party testing institute. Testing equipment tolerances will be applied to all actual power output measurements.
- 2.3 In the event it is determined that there is a negative deviation of actual performance from the warranted values then SpolarPV, at its option, will compensate for such loss in power by either providing to the Buyer additional modules to make up the total wattage loss, or by repairing or replacing the modules or providing an appropriate residual market value of the product(s) as compensation.

SpolarPV Technology Co., Ltd

Maoshan Road 39, Gaochun Economic Development Zone, Nanjing, Jiangsu, China

LIMITED WARRANTY STATEMENT PHOTOVOLTAIC MODULE PRODUCTS



3. Exclusions and Limitations

- **3.1** Warranty claims must in any event be filed within the applicable warranty period.
- **3.2** The limited warranties do not apply to any PV modules which, in SpolarPV absolute judgment, have been subjected to:
 - Misuse, abuse, neglect or accident;
 - Alternation, improper installation or application;
 - Non-observance of SpolarPV's installation-users and maintenance instructions;
 - Repair or modifications by someone other than a qualified service technician;
 - Power failure surges, lighting, flood, fire, accidental breakage or other events outside SpolarPV's control;
 - Any move and subsequent installation of the module.
- **3.3** The limited warranties do not cover any shipping costs for the return of the PV modules, or for reshipment of any repaired or replaced PV modules, or cost associated with installation, removal or reinstallation of the PV modules.
- **3.4** Warranty claims will not be honored if the type or serial number of the PV modules have been altered, removed or made illegible. All other statements made by SpolarPV (including without limitation to those made in the SpolarPV's promotional materials) in respect of the properties, performance characteristics and other aspects of the modules are for illustration only and are not legally binding on SpolarPV. To the fullest extent permitted by law, SpolarPV excludes all implied representations and warranties in respect of the modules, their properties and performance characteristics. To the fullest extent permitted by law, SpolarPV also excludes all liabilities to the Buyer and any user of the PV modules produced by SpolarPV for any loss of actual or anticipated profits, revenues, turnover, anticipated savings, business or goodwill.

4.Disputes

No action, regardless of form, arising out of or in any way connected with this limited warranty policy, may be brought by the Buyer more than one (1) year after the cause of action has accrued.

5. Various

The repair or replacement of the PV modules or the supply of additional PV modules does not cause the beginning of new warranty terms, nor shall the original terms of this limited warranty be extended. Any replaced PV modules shall become the property of SpolarPV. SpolarPV has the right to deliver another type (different in size, color, shape and /or power) in case SpolarPV discontinues producing the PV-module in question at the time of the claim.

SpolarPV Model Family Form

	opolali v	Widder I allilly		
Model Name	Rated Power [Wp]	Australia CEC	Dimensions [length x width x height]	Number of cells
	I ower [Wp]	Model type		
		166 Cell		
		½ cut of 166 mono c-Si		
SPVxxx-PM6-144	420-460	SPV450-PM6-144 SPV440-PM6-144	2094*1038*30	144
SPVxxx-PM6-132	385-420		1924x1038x30	132
SPVxxx-PM6-120	350-385	SPV375-PM6-120	1754*1038*30	120
SPVxxx-PM6-108	315-345		1580*1038*30	108
SPVxxx-PM6-96	280-305		1580*1038*30	96
SPVxxx-PM6-72	210-230		1580*702*30	72
		166 mono c-Si cell,bifacia		
SPVxxx-PM6-144BS	420-460		2094*1038*30	144
SPVxxx-PM6-132BS	385-420		1924x1038x30	132
SPVxxx-PM6-120BS	350-385		1754*1038*30	120
SPVxxx-PM6-108BS	315-345		1580*1038*30	108
SPVxxx-PM6-96BS	280-305		1580*1038*30	96
SPVxxx-PM6-72BS	210-230		1580*702*30	72
		182 Cell		
	With 1	½ cut of 182 mono c-Si	cell:	
SPVxxx-PM10-156	300-600		2464*1133*30	156
SPVxxx-PM10-144		SPV550-PM10-144	2278*1133*30	144
	275-555	SPV540-PM10-144		
		SPV430-PM10-144 SPV500-PM10-132	2094*1133*30	132
SPVxxx-PM10-132	250-505	SPV390-PM10-132	2004 1100 00	102
SPVxxx-PM10-120		SPV450-PM10-120	1902*1133*30	120
	230-460	SPV440-PM10-120		
SPVxxx-PM10-108	205-415	SPV350-PM10-120 SPV410-PM10-108 SPV400-PM10-108 SPV330-PM10-108 SPV315-PM10-108 SPV280-PM10-108 SPV220-PM10-108	1721*1133*30	108
SPVxxx-PM10-96	185-370	01 V220-1 W110-100	1540*1133*30	96
SPVxxx-PM10-72	135-275		1724*766*30	72
SPVxxx-PM10-60	115-230		1134*988*30	60
SPVxxx-PM10-48	90-185		1173*766*30	48
SPVxxx-PM10-36	70-140		1134*618*30	36
		182 mono c-Si ce ll ,bifacia		
SPVxxx-PM10-156BS	300-600		2464*1133*30	156
SPVxxx-PM10-144BS	275-555		2278*1133*30	144
SPVxxx-PM10-132BS	250-505		2094*1133*30	132
SPVxxx-PM10-120BS	230-460		1902*1133*30	120
SPVxxx-PM10-108BS	205-415		1721*1133*30	108
SPVxxx-PM10-96BS	185-370		1540*1133*30	96
SPVxxx-PM10-72BS	135-275		1724*766*30	72
SPVxxx-PM10-60BS	115-230		1272*766*30	60
SPVxxx-PM10-48BS	90-185		1200*766*30	48
SPVxxx-PM10-36BS	70-140		1135*766*30	36

Model Name	Rated Power [Wp]	Australia CEC Model type	Dimensions [length x width x height]	Number of cells in module		
210 Cell						
With ½ cut of 210 mono c-Si cell:						
SPVxxx-PG12-132	640-670	SPV660-PG12-132	2383*1302*30	132		
SPVxxx-PG12-120	580-610	SPV600-PG12-120 SPV595-PG12-120	2171*1302*30	120		
SPVxxx-PG12-110	535-555		2383*1095*30	110		
With ½ cut of 210 mono c-Si cell:bifacial single glass;						
SPVxxx-PG12-132BS	640-670		2383*1095*30	132		
SPVxxx-PG12-120BS	580-610		2383*1095*30	120		
SPVxxx-PG12-110BS	535-555		2383*1095*30	110		
With 1/₃ cut of 210 mono c-Si cell: third-cut cells;						
SPVxxx-PG12-T150	480-520		2383*1095*30	150		
SPVxxx-PG12-T120	385-415		2383*1095*30	120		
With ⅓ cut of 210 mono c-Si cell:third-cut cells,bifacial single glass						
SPVxxx-PG12-T150BS	480-520		2383*1095*30	150		
SPVxxx-PG12-T120 BS	385-415		2383*1095*30	120		

Australian Importer: Renewable Energy Laboratory Pty Ltd.

Add: 402-24 Rochester St, Botany, NSW2019, Australia

ABN:56090407346

Contact:Zi Ouyang

Email:zi.ouyang@pvmaster.com

Mobile: +61 4 3028 2259

www.pvmaster.com